



Part Number: 9926

Hook- Up/ Lead Wire UL AWM Style 1007 & 1569, (1) 26 AWG (7x34) TC, PVC, 300V 80°C, 300V 105°C

Request Sample

# **Product Description**

One 26 AWG stranded (7x34) tinned copper conductor, PVC insulation.

# **Technical Specifications**

## **Physical Characteristics (Overall)**

Conductor				
AWG	Stranding	Mate	rial	No. of Conductors
26	7x34	TC - Tinned	d Copper	1
Conductor Count: 1				
Condu	Conductor Size: 26		26 AWC	}

#### Insulation

Material	Nominal Diameter	Nominal Wall Thickness	Min. Average Wall Thickness
PVC - Polyvinyl Chloride	0.051 in	0.016 in	0.015 in

#### **Outer Jacket Material**



#### **Electrical Characteristics**

Shielding:	Unshielded
Voltage	

Non-UL Voltage Rating	UL Voltage Rating
300 V	300 V

# **Temperature Range**

Non-UL Temp Rating:	105°C
UL Temp Rating:	105°C

### **Mechanical Characteristics**

Bulk Cable Weight:	1.9 lbs/1000ft
Max Recommended Pulling Tension:	3.5 lbs

#### **Standards**

UL Rating:	300V RMS, 80°C and 300V, 105°C
UL AWM Style:	UL Style 1007 (300 V 80°C), UL Style 1569 (300 V 105°C)
CSA Rating:	300V RMS, 105°C
CSA AWM Specification:	TRSR-64
CSA Type:	TRSR-64
Military Specification:	N/A

# **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes			

EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-10-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
CSA Flammability:	FT1
UL voltage rating:	300 V RMS

#### Plenum/Non-Plenum

Plenum (Y/N): No	
	Plenum (Y/N):

#### **Part Number**

#### Variants

Item #	Color	Footnote
9926 010100	Black	
9926 0101000	Black	Р
9926 0131000	Blue, Dark	Р
9926 0011000	Brown	Р
9926 0081000	Gray	Р
9926 0051000	Green, Dark	Р
9926 0031000	Orange	Р
9926 002100	Red	
9926 0021000	Red	Р
9926 0071000	Violet	Р
9926 0091000	White	Р
9926 0041000	Yellow	Р

Footnote: P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'.

# © 2018 Belden, Inc

# All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.